

DECK-OVER TILT



STANDARD FEATURES

- Mainframe:** 10" x 19 lb Beam on Trailers up to 30 Feet - 30 Feet Plus Trailers Have 10" x 22 lb Beam
- Coupler:** Bumper Pull - 40K" Adjustable Pintle
Gooseneck- 2-5/16" Adjustable Coupler
- Deck:** 2" x 10" Treated Douglas Fir
- Trailer Width:** 96.5"
- Deck Length:** Standard is 3' Stationary/ 23' Tilt
- Deck Height:** 36"
- Tilt Angle:** 11 Degree
- Dexter Axles:** 20K Model: Tandem Dually 10K Slipper Springs
24K Model: Tandem Dually 12K Slipper Springs
- Tires:** 235/80R16 E on 8-Hole Wheel Dually
- Brakes:** Electric
- Landing Gear:** Dual 12K Spring Loaded Drop-Foot Jacks
- Ramps:** 2' Flip-Over Ramps
- Tie Downs:** 1" D- Rings (6 Per Side)
- Spare Mount:** KTP Model - Mounted on Tongue
KTG Model - Mounted on Gooseneck
- Chain Box:** Includes Locking Lid
- Cross Members:** 4" Channel
- Lights:** DOT Approved LED Sealed Beam With Rubber Grommet
- Wiring:** DOT Modular Wiring Harness
- Safety:** Reflective Tape, Safety Chains with Hooks, Break-Away Switch with Battery Charger
- Finish:** Black Powder Coat Finish
- Warranty:** One Year Limited Structure

KTG Gooseneck Models

Model	GVWR	Empty Weight*
20 KTG	20,000 #	7,200 #
24 KTG	24,000 #	7,400 #

* Empty weights are approximations. It is the customers responsibility to verify exact weight.

KTP Bumper Pull Models

Model	GVWR	Empty Weight*
20 KTP	20,000 #	6,800 #
24 KTP	24,000 #	7,000 #

Larger GVWR Models Available

* Empty weights are approximations. It is the customers responsibility to verify exact weight.

OPTIONAL EQUIPMENT

- Option 1** Tilt - Hydraulic Power Unit
- Option 2** Tilt - Metering Valve (Controls Rate)
- Option 3** Jack - Dual Speed
- Option 4** Additional 1" D-Rings
- Option 5** Tire - Spare Dually
- Option 6** Extra Length
- Option 7** Stake Pockets, Spools, & Rubrail
- Option 8** Gray Powder
- Option 9** Other Powder

Walton Trailers

866-653-5444

www.waltontrailers.com

©Copyright 2014 Walton Trailers, LLC. All rights reserved.

QUALITY

DEPENDABILITY

DURABILITY